

Registration No.:

| | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|

Total Number of Pages: 02

Course: B.Tech
Sub_Code: RC17D006

7th Semester Regular/Back Examination: 2024-25
SUBJECT: Water Resource Engineering
BRANCH(S): C&EE, CIVIL
Time: 3 Hours
Max Marks: 100
Q.Code: R110

Answer Question No.1 (Part-1) which is compulsory, any eight from Part-II and any two from Part-III.

The figures in the right hand margin indicate marks.

Part-I

Q1 Answer the following questions: (2 x 10)

- What type of rainfall data is recorded in the Tipping-bucket type rain gauge and Weighing-bucket type rain gauge?
- How is the consistency of precipitation data tested?
- How is the storage volume of a reservoir calculated from a mass curve?
- What is effective rainfall, and how is it determined in hydrograph analysis?
- What is flood routing, and why is it necessary in hydrology?
- How does frequency analysis help in flood estimation?
- What is critical depth in open channel flow?
- A hydraulic jump occurs in a horizontal rectangular channel with a flow depth of 2m and 3m before and after the jump. Calculate the energy dissipation head.
- The Froude number of a flow in a rectangular channel is 0.73. If the depth of flow is 1.50 m, find the specific energy.
- Differentiate supercritical and subcritical depth.

Part-II

Q2 Only Focused-Short Answer Type Questions- (Answer Any Eight out of Twelve) (6 x 8)

- Describe the depth-area-duration relationships in precipitation and their application in hydrological studies.
- Explain ϕ -index and W-Index. The average rainfall over 45 ha of a watershed for a particular storm is given below. The volume of runoff from this storm was determined as 2.25 ha-m. Determine w-index and ϕ -index.

| | | | | | | | | |
|---------------|---|-----|-----|------|-----|-----|-----|---|
| Time (hr) | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| Rainfall (cm) | 0 | 0.5 | 1.0 | 3.25 | 2.5 | 1.5 | 0.5 | 0 |

- What is the SCS-CN method for estimating runoff volume? Describe how it is applied in hydrological modeling.
- Discuss the use of flow duration curves and flow-mass curves in streamflow analysis.
- Explain the factors affecting a runoff hydrograph and how these factors are used to interpret hydrographs.
- What is base flow separation, and how is it performed in hydrograph analysis?

- g) What is the return period, and what is its significance of it?
A one-day rainfall of 20.0 cm at place X was found to have a period of 100 years. Calculate the probability that a one-day rainfall of magnitude equal to or larger than 20.0 cm:
(i) It will not occur at station X during the next 50 years.
(ii) It will happen in the next year.
- h) Define drought and classify it based on different characteristics.
- i) Define uniform flow in open channels and explain the Chezy and Kutter equations for flow estimation.
- j) Describe gradually varied flow in open channels and the factors that affect its behavior.
- k) Explain the concept of non-uniform flow and the factors that influence it.
- l) In a 4.0-m wide rectangular channel ($n = 0.017$), the bed slope is 0.0006. When the channel is conveying $50 \text{ m}^3/\text{s}$ of flow, estimate the nature of GVF profiles at two far away sections, P and R, in this channel where the depth of flow is measured as 1.6 m and 2.1 m, respectively.

Part-III

Only Long Answer Type Questions (Answer Any Two out of Four)

- Q3 (a) Explain the maximum intensity/depth-duration-frequency relationship in relation to rainfall events. (8)
- (b) The following are the ordinates of the hydrograph of flow from a catchment area of 800 km^2 due to a 6-h rainfall. Derive the ordinates of the 6-h unit hydrograph. Make suitable assumptions regarding the base flow. (8)

| | | | | | | | | | | | | | |
|-------------------------------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|
| Time (h) | 0 | 6 | 12 | 18 | 24 | 30 | 36 | 42 | 48 | 54 | 60 | 66 | 72 |
| Discharge (m^3/s) | 40 | 65 | 215 | 360 | 400 | 350 | 270 | 205 | 145 | 100 | 70 | 50 | 42 |

- Q4 (a) Explain the Sequent Peak Procedure and its use in reservoir planning and flood control. (8)
- (b) What are synthetic unit hydrographs, and how are they used in flood estimation? (8)
- Q5 (a) Describe channel routing in the context of flood management and explain its importance in hydrological studies. (8)
- (b) Determine the dimensions of a concrete-lined ($n = 0.012$) trapezoidal channel of efficient proportions to carry a discharge of $12.5 \text{ m}^3/\text{s}$. The bed slope of the channel is 0.0005 and side slope = 3:4. (8)
- Q6 (a) What is the most economical cross-section in open channel flow design, and how is it determined? (8)
- (b) What is a hydraulic jump in open channel flow, and how does it affect water flow and energy dissipation? (8)